§ 382.93

the departing flight. It is permissible for the two carriers to mutually agree that the carrier operating the departing connecting flight (i.e., the second flight of the two) will provide this assistance, but the carrier operating the arriving flight remains responsible under this section for ensuring that the assistance is provided.

- (b) You must also provide or ensure the provision of assistance requested by or on behalf of a passenger with a disability, or offered by carrier or airport operator personnel and accepted by a passenger with a disability, in moving from the terminal entrance (or a vehicle drop-off point adjacent to the entrance) through the airport to the gate for a departing flight, or from the gate to the terminal entrance (or a vehicle pick-up point adjacent to the entrance after an arriving flight).
- (1) This requirement includes assistance in accessing key functional areas of the terminal, such as ticket counters and baggage claim.
- (2) This requirement also includes a brief stop upon the passenger's request at the entrance to a rest room (including an accessible rest room when requested). As a carrier, you are required to make such a stop only if the rest room is available on the route to the of destination the enplaning. deplaning, or connecting assistance and you can make the stop without unreasonable delay. To receive such assistance, the passenger must self-identify as being an individual with a disability needing the assistance.
- (c) As a carrier at a U.S. airport, you must, on request, in cooperation with the airport operator, provide for escorting a passenger with a service animal to an animal relief area provided under §382.51(a)(5) of this part.
- (d) As part of your obligation to provide or ensure the provision of assistance to passengers with disabilities in moving through the terminal (e.g., between the terminal entrance and the gate, between gate and aircraft, from gate to a baggage claim area), you must assist passengers who are unable to carry their luggage because of a disability with transporting their gate-checked or carry-on luggage. You may request the credible verbal assurance that a passenger cannot carry the lug-

gage in question. If a passenger is unable to provide credible assurance, you may require the passenger to provide documentation as a condition of providing this service.

§ 382.93 Must carriers offer preboarding to passengers with a disability?

As a carrier, you must offer preboarding to passengers with a disability who self-identify at the gate as needing additional time or assistance to board, stow accessibility equipment, or be seated.

§ 382.95 What are carriers' general obligations with respect to boarding and deplaning assistance?

- (a) As a carrier, you must promptly provide or ensure the provision of assistance requested by or on behalf of passengers with a disability, or offered by carrier or airport operator personnel and accepted by passengers with a disability, in enplaning and deplaning. This assistance must include, as needed, the services of personnel and the use of ground wheelchairs, accessible motorized carts, boarding wheelchairs, and/or on-board wheelchairs where provided in accordance with this part, and ramps or mechanical lifts.
- (b) As a carrier, you must, except as otherwise provided in this subpart, provide boarding and deplaning assistance through the use of lifts or ramps at any U.S. commercial service airport with 10,000 or more annual enplanements where boarding and deplaning by levelentry loading bridges or accessible passenger lounges is not available.

§ 382.97 To which aircraft does the requirement to provide boarding and deplaning assistance through the use of lifts apply?

The requirement of section 382.95(b) of this part to provide boarding and deplaning assistance through the use of lifts applies with respect to all aircraft with a passenger capacity of 19 or more, with the following exceptions:

- (a) Float planes;
- (b) The following 19-seat capacity aircraft models: the Fairchild Metro, the Jetstream 31 and 32, the Beech 1900 (C and D models), and the Embraer EMB-120: